

## Herkules 5020 Door and Bumper Jack

Due to shipping regulations, this Door and Bumper Jack is shipped partially assembled. In addition to the base, tower with 4 adjustment holes and tower extension, the box contains the following parts for assembly.

- (4) 3" casters and nuts
- (6) 1" square end plugs
- (2) Bumper hooks
- (1) Bent rubber coated rod
- (1) Straight Rubber Coated Rod
- (1) Plastic knob with threaded ste
- (2) Chains
- (2) Wing nuts
- (2) 1/4" x 3/4" Bolts
- (12) 1-1/2" square end plugs
- (4) Flat Washers
- (2) Fender Washers



## ASSEMBLY INSTRUCTIONS

1. The chain assembly bumper hooks must be clicked onto the snap links found on the cradle. Assemble the bumper hooks with the hardware and chain included in the packing.
2. At the unit base, use the 5/16" nut and lock washers to install the casters in the pre-drilled holes. The square finishing caps enable sealing the ends of the tubing, after you have the casters securely in place.
3. Position the plunger inside the center vertical tube (that extends from the base). Place the plunger so that the extension arms extend over the cradle of this Door and Bumper Dolly, and secure it with a plastic knob.

4. Attach the straight and bent rubber coated rods to the tower extension, using two fender washers and two wing nuts. Insert the rod through the gap in the extension, and place the fender washer over it. The wing nuts can be used to hold the structure firmly in place.